



Analytical Instruments
Raised To Excellence


LABSOLUTIONS

ARE/AREX-6 Series Hot Plate Stirrers

Superior Performance & Absolute Safety




ACCURATE THERMOREGULATION



SPEEDSERVO™



CERALTOP™



PROTECTION



SAFETY



PRODUCTIVITY



AREX-6 Connect PRO

The VELP AREX-6 Connect PRO is the first hot plate stirrer with embedded Wi-Fi technology to monitor and control your reactions through VELP Ermes cloud platform.

ABSOLUTE SAFETY

The safety standards of the AREX-6 Series meet the potential of cloud-based services giving the possibility to control the instrument remotely and interrupt the operations with a click.

YOUR HOT PLATE STIRRER IN REAL TIME

With the AREX-6 Connect PRO is possible to monitor in real time the reactions and the instrument working conditions from any device (PC, Tablet and Smartphone) and to be informed with immediate notifications (dashboard and email)

DATA MANAGEMENT


Safely access to your data with different clearance levels, create and share reports with your peers in many different file format.

GET ALWAYS THE BEST FEATURES

The AREX-6 Connect PRO receives OTA (Over-the-Air) Software Updates to get new features and enhancement in order to achieve the maximum lifespan.

EASY AND SMART

The connection to VELP Ermes platform is easy and safe and it takes only few minutes to benefit of the cloud-based potential and the smart user experience of the platform.



ermes enabled

CONFIGURATIONS



AREX-6 Connect PRO System with Probe



AREX-6 Connect PRO System with Probe, Rod and Clamp

AREX-6 Digital & Digital PRO

The AREX-6 Digital versions are the most advanced VELP hot plate stirrers offering supreme performance, superior safety features and ease-of-use. The connection with the external temperature probe Pt100 and digital thermoregulators VTF and VTF EVO ensures top class versatility meeting all temperature accuracy requirements.

SAFE HEATING CONTROL

Two independent temperature safety circuits switch off the heating in case of overtemperature (different from the set point).

ADVANCED THERMOREGULATION

Fast, precise and stable temperature control with minimal overshoot. Excellent heat transfer with CerAlTop™ plate. Able to reach a maximum temperature of 370°C.

POWERFUL MAGNET

The Alnico magnet provides leading magnetic coupling and guarantees superior peripheral stirring. Maximum speed of 1700 rpm, SpeedServo™ torque compensation.

UNATTENDED OPERATIONS

The built-in timer switches the main function off after the set running time.

ENHANCED KINETICS

The Auto-Reverse of stirring direction is a key feature for improving mixing effectiveness.

SMART USER INTERFACE

The new icons and display ensure a clear readout of the working conditions and warning messages such as HOT TOP.



CONFIGURATIONS



AREX-6 Digital System with Probe



AREX-6 Digital System with Probe, Rod and Clamp



AREX-6 Digital PRO System with VTF and Rod



AREX-6 Digital PRO System with VTF EVO, Rod and Wireless DataBox™

AREX-6

The AREX-6 is the safe and powerful analog hot plate stirrer with CerAlTop™ plate guaranteeing excellent heat transfer and resistance to chemicals. The powerful motor and Alnico magnet stir up to 20 liters at a maximum speed of 1700 rpm.

UPGRADE TO DIGITAL

For superior performance you can upgrade the AREX-6 by connecting one of the VELP Digital Thermoregulators VTF or VTF EVO:

- Direct temperature control of the sample with 0.5°C accuracy.
- The VTF EVO Wireless allows the operator to control all the temperature parameters directly from the PC.

Safety Heating Switch



CONFIGURATIONS



ARE-6

The ARE-6 is the safe and powerful analog hot plate stirrer for applications that do not require accurate temperature control of the medium. The ARE-6 incorporates high level features such as the Alnico magnet with top class magnetic coupling and SpeedServo™ torque compensation.

BASIC HIGH PERFORMANCE SOLUTION

The aluminum alloy top plate offers optimum heat transfer and chemical resistance.

The independent luminous safety switch prevents unintentional heating and indicates when heating is On.

The heating icon illuminates when the plate temperature is above 50°C acting as a HOT TOP warning system.

Safety Heating Switch



CONFIGURATIONS



Improve your productivity

ALUBLOCK™

The new MonoAluBlock™ and MultiAluBlock™ are used to perform numerous reactions reducing time and bench space.

- **MonoAluBlock™** is the ideal solution for multiple vials of the same dimensions.
- **MultiAluBlock™** are combinable segments for different sizes of vials. Mix and match according to need.



A00000323 MultiAluBlock™ Base	A00000324 MultiAluBlock™ 4 pos. Ø28xh.43 mm	A00000325 MultiAluBlock™ 4 pos. Ø28xh.30 mm	A00000326 MultiAluBlock™ 4 pos. Ø28xh.24 mm	A00000327 MultiAluBlock™ 4 pos. Ø21xh.31 mm	A00000328 MultiAluBlock™ 8 pos. Ø17xh.26 mm	A00000329 MultiAluBlock™ 11 pos. Ø15xh.20 mm	A00000337 MultiAluBlock™ 11 pos. Ø12xh.14 mm	A00000340 MonoAluBlock™ 17 pos. Ø28xh.43 mm	A00000339 MonoAluBlock™ 17 pos. Ø28xh.30 mm	A00000338 MonoAluBlock™ 17 pos. Ø28xh.24 mm	A00000341 MonoAluBlock™ 40 pos. Ø12xh.14 mm

HEMISPHERIC BOWLS & PTFE COVERS

The **Hemispheric Bowls** replace oil baths and mantles for clean and safe analysis with round bottom flasks. VELP Hemispheric Bowls fit the Ø 135mm plate ensuring **fast plate-flask heat transfer**.

PTFE Safety covers are designed to minimize thermal dispersion and increase safety.

A00000373 Hemispheric bowl for 25 ml flasks	A00000330 Hemispheric bowl for 50 ml flasks	A00000331 Hemispheric bowl for 100 ml flasks	A00000332 Hemispheric bowl for 250 ml flasks	A00000333 Hemispheric bowl for 500 ml flasks	A00000334 Hemispheric bowl for 1000 ml flasks	A00000374 Hemispheric bowl for 3 L flasks	A00000375 Hemispheric bowl for 5 L flasks	PTFE Safety cover Available for each size



PTFE SAFETY COVERS

* PTFE Safety Cover Hemispheric Bowl 50 ml	A00000342
* PTFE Safety Cover Hemispheric Bowl 100 ml	A00000343
* PTFE Safety Cover Hemispheric Bowl 250 ml	A00000344
* PTFE Safety Cover Hemispheric Bowl 500 ml	A00000345
* PTFE Safety Cover Hemispheric Bowl 1000 ml	A00000346



STIRRING BARS & ACCESSORIES

Protective cover ARE/AREX-6 series	A00000335
Magnetic stir bar, Ø3x6 mm	A00001062
Magnetic stir bar, Ø4,5x12 mm	A00001063
Magnetic stir bar, Ø6x20 mm	A00001057
Magnetic stir bar, Ø6x35 mm	A00001056
Magnetic stir bar Ø8x40 mm	A00000356
Magnetic stir bar, Ø10x60 mm	A00001061
Magnetic cross shape stir bar, Ø10x5mm	A00000336
Magnetic cross shape stir bar, Ø20x8 mm	A00000352
Magnetic disc stir bar, Ø10x6 mm	A00000354
Magnetic disc stir bar, Ø20x10 mm	A00000355
Magnetic octagonal stir bar, Ø10x13 mm	A00000357
Support rod	A00001069
Handle for AluBlock™ removal	A00000351
Clamp with probe support	A00000280
VTF EVO Digital Thermoregulator whitout DataBox™	F208B0064



EXTERNAL TEMPERATURE SENSORS

Temperature probes and thermoregulators ensure precise temperature control for accurate and reproducible results.



CONFIGURATIONS CODES

		ARE-6	AREX-6	AREX-6 Digital	AREX-6 Digital PRO	AREX-6 Connect PRO
STIRRER ONLY	230 V / 50-60 Hz 115 V / 60 Hz	F20500462 F20510462	F20500463 F20510463	- -	- -	- -
WITH PT100 TEMPERATURE PROBE	230 V / 50-60 Hz 115 V / 60 Hz	- -	- -	SA20500461 SA20510461	- -	SA20500465 SA20510465
WITH PT100, SUPPORT ROD AND CLAMP	230 V / 50-60 Hz 115 V / 60 Hz	- -	- -	SB20500461 SB20510461	- -	SB20500465 SB20510465
WITH VTF AND SUPPORT ROD	230 V / 50-60 Hz 115 V / 60 Hz	- -	SA20500463 SA20510463	- -	SB20500460 SB20510460	- -
WITH VTF AND SUPPORT ROD and Wireless DataBox™	230 V / 50-60 Hz 115 V / 60 Hz	- -	SB20500463 SB20510463	- -	SC20500460 SC20510460	- -

TECHNICAL DATA

	ARE-6	AREX-6	AREX-6 Digital	AREX-6 Digital PRO	AREX-6 Connect PRO
USER INTERFACE	Analog	Analog	Digital	Digital	Digital
MOTOR	Brushless	Brushless	Brushless	Brushless	Brushless
PLATE MATERIAL	Aluminum Alloy	CerAlTop™ (ceramic coated aluminum alloy)			
PLATE DIAMETER	135 mm	135 mm	135 mm	135 mm	135 mm
STIRRING VOLUME (H2O)	Up to 20 L	Up to 20 L	Up to 20 L	Up to 20 L	Up to 20 L
STIRRING SPEED RANGE	30-1700 rpm	30-1700 rpm	30-1700 rpm	30-1700 rpm	30-1700 rpm
SPEED ACCURACY	-	-	5 rpm	5 rpm	5 rpm
SPEED CONTROL	Analog	Analog	Digital	Digital	Digital
TORQUE COMPENSATION	SpeedServo™	SpeedServo™	SpeedServo™	SpeedServo™	SpeedServo™
TEMPERATURE RANGE	Room temp. - 370 °C	Room temp. - 370 °C	Room temp. - 370 °C	Room temp. - 370 °C	Room temp. - 370 °C
HEAT CONTROL	Analog	Analog	Digital	Digital	Digital
HEAT SETTING RESOLUTION	Scale	Scale	1°C	1°C	1°C
EXTERNAL DIGITAL THERMOREGULATORS CONNECTION	-	VTF / VTF EVO	-	VTF / VTF EVO	VTF / VTF EVO
EXTERNAL PROBE CONNECTION	-	-	Pt100 (Included)	Pt100	Pt100 (Included)
MEDIUM HEAT CONTROL ACCURACY	-	±0.5°C (VTF/VTFEVO)	±1°C (Pt100)	±0.5°C (VTF/VTFEVO) ± 1 °C (Pt100)	±0.5°C (VTF/VTFEVO) ± 1 °C (Pt100)
TIMER	-	-	Yes	Yes	Yes
AUTO-REVERSE	-	-	Yes	Yes	Yes
PROBE DETECTOR	-	-	Yes	Yes	Yes
HOT TOP WARNING SYSTEM	Illuminated Icon	Illuminated Icon	On Display	On Display	On Display
ON/OFF SAFETY-HEATING-SWITCH	Yes	Yes	Yes	Yes	Yes
PROTECTION CLASS	IP 42	IP 42	IP 42	IP 42	IP 42
DIMENSIONS (WxHxD)	160x105x280 mm 6.5x4.1x11 in	160x105x280 mm 6.5x4.1x11 in	160x105x280 mm 6.5x4.1x11 in	160x105x280 mm 6.5x4.1x11 in	160x105x280 mm 6.5x4.1x11 in
PERMISSIBLE AMBIENT TEMPERATURE	5-40 °C	5-40 °C	5-40 °C	5-40 °C	5-40 °C
POWER INPUT	630 W	630 W	630 W	630 W	630 W
WEIGHT	2.6 Kg 5.7 lb	2.6 Kg 5.7 lb	2.6 Kg 5.7 lb	2.6 Kg 5.7 lb	2.6 Kg 5.7 lb
ERMES CONNECTION	-	-	-	-	Yes



SERVICE & SUPPORT

VELP Scientifica products are designed by our engineers to resist years of laboratory use.

Our products are manufactured with premium materials to guarantee the best performance with maximum safety.

According to our experience, a proper and regular maintenance is necessary to ensure the highest performance of analytical instrument. VELP Service Department and VELP Official Partners are always ready to offer you maintenance and service support tailored to your needs.

GET THE SUPPORT YOU NEED CHOOSING THE OPTIONS:

- Help-desk and Remote support
- Technical Assistance
- Analytical Support



We reserve the right to make technical alterations.
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner

DESIGNED AND MANUFACTURED IN ITALY



ITALY – HQ
Via Stazione 16
20865 Usmate (MB) Italy
Tel. +39 039 628811
velpitalia@velp.com

INDIA
velpindia@velp.com

USA
155 Keyland Court, Bohemia
NY 11716 - U.S.
Tel. +1 631 573 6002
velpusa@velp.com

CHINA
velpchina@velp.com