



PRODUCT CATALOGUE 2022





Mass Comparators





Automatic Vacuum Mass Comparators

AVK-1000

Automatic Vacuum Mass Comparator

The AVK-1000 automatic vacuum mass comparator is mainly intended for national metrological institutes that transport and maintain the national reference mass standard of 1 kg.

Resolution of 10 billion units plus elimination of human error and other external factors due to the use of vacuum chamber effectively prevent any potential errors that may occur during the measurement.

The comparator enables comparison of up to 6 artefacts of cylinder or sphere shape, and of max 1 kg mass, with repeatability of 0.5 µg and readability of 0.1 µg. Thanks to a suspended weighing pan, the eccentricity error being an effect of incorrectly positioned mass standard is eliminated.

A specially designed vacuum chamber enables carrying out measurements in a vacuum of 10^{-6} mBar capacity or in atmosphere containing noble gases, also in constant pressure upon closing the system with use of the top-class quality valves.

LOAD LOCK mass standard transfer system enables switching or adding artefacts without changing the atmosphere inside the main chamber. Use of mass standard transfer chamber reduces time required for obtaining the respective value of vacuum to ca. 4 hours. the LOAD LOCK is equipped with a high-efficiency pump system and a top-class vacuum gauge. a specially designed inspection hole enables monitoring of the whole transfer process. Supplementing the AVK-1000 vacuum mass comparator with LOAD LOCK system significantly improves the comparison performance.



Used chamber enables comparison in vacuum of maximum 10^{-6} mBar or in noble gases such as argon.



The LOAD LOCK system for transfer of mass standards enables switching and adding artefacts without changing the atmosphere inside the main chamber.



The mass comparator features magazine for 6 cylindrical objects of $\varnothing(22 - 95) \times 110$ mm or sphere objects of maximum diameter of $\varnothing 100$ mm.



Suspended weighing pan of custom design eliminates eccentricity errors and facilitates dropping the weight onto the magazine insert correctly.



Density Measurement
Mass Comparators

AGV

Automatic Comparators

RADWAG-designed AGV automatic comparator uses the most accurate method of determining density of mass standard. First, the mass standard is weighed in air and then in liquid of known density. Specially designed construction of the weighing pan minimizes the influence of surface tension of the liquid.

The comparator is equipped with a top-class thermometer of 0.001°C resolution and three temperature sensors. Measurement carried out in three points of the container (at the bottom, in the middle and near the surface) allows to assess the difference in temperature. With this, it is possible to mix and even the liquid temperature in the container. Otherwise, the density measurement results may be incorrect.

The comparator software enables to determine mass standards density and calculate uncertainty using a method according to OIML R111. it also allows to determine (verify) liquid density.


5.7" colour touch screen ensures comfort of comparator operation. Easy access to numerous applications and functions is ensured by home screen customization. the indicator is equipped with two programmable proximity sensors.



Special design of the insert ensures very high measuring range of the comparator (1g-1kg). it is also intended for comparison of silicone spheres.



The comparator features specially designed feeder to load and unload the magazine with mass standards.



Dedicated software for determination of mass standard's density and volume.




A weighing pan suspended on wires of 0.3 mm diameter significantly minimizes the eccentricity and eliminates the influence of liquid surface tension.



Mini Robotic Mass Comparators

RMCM

Robotic Mass Comparators



The mass standard magazine offers up to 120 magazine positions.



The mass comparator facilitates a complete dissemination process.



Remote preview of comparison process in real time is possible thanks to a video camera.



The mass comparator allows real-time monitoring of ambient conditions.

Combination of the mass comparator and the robotic transport system has resulted with development of a new RADWAG mass comparator, the RMCM. The device is unique due to its compact dimensions and aesthetic look.

This combination brings a number of advantages:

- reduction of air drafts and vibrations from a robotic system in the course of comparison,
- minimised human error risk,
- compact dimensions,
- easier maintaining of stable environmental conditions inside the weighing chamber.

The mass comparator comes standard with a top-class thermo-hygro-barometer enabling real-time control of ambient conditions in three locations. The characteristic feature of the device is high readability of pressure, 0.001 hPa, humidity, 0.01 %, and temperature, 0.001 °C. Reliability of ambient conditions measurement carried out using the thermo-hygro-barometer is confirmed by a calibration certificate.

Mechanical design of the mass standard magazine insert allows measurement of extremely small mass with very high accuracy, and prevents weight jamming. The device enables comparison of weights of all shapes compliant with OIML recommendations, using just one universal insert.



Robotic Mass Comparators

RMC

Robotic Mass Comparators

The new line of RADWAG-manufactured RMC robotic mass comparator ensures repeatability of measurements ranging from 1 g to 1 kg with readability of 0.1 µg. The device is equipped with two magazines, 100-position one and additional 2-position magazine enabling dissemination of the mass standard into maximum 3 mass standards (e.g. 50 g mass standard can be disseminated into 3 mass standards of 20 g, 20 g and 10 g). Locating additional magazine near mass comparator weighing pan significantly shortens the calibration process.

RMC robotic mass comparator, due to the elimination of the human factor, temperature changes and air drafts, guarantees excellent measurement repeatability. Intermediate mass standard magazine enables storing mass standards near the weighing pan. With this the calibration time is reduced to minimum.

Insert design of the mass standard magazine allows measurement of weight of very small mass with high accuracy and prevents weight jamming. The device enables comparison of weight of various shapes using just one universal insert.



RADWAG as the worldwide pioneer has adopted the possibilities of the automatic mass comparator into the robotic comparison system. This modern approach has improved comparison result repeatability by 100% in relation to standard solutions applied worldwide.



Feeder of custom design enables fast and precise comparison and dissemination.



The mass comparator enables a complete dissemination process, which is possible due to placing the intermediate mass standard magazine inside the mass comparator chamber. This significantly shortens comparison duration and reduces wear and tear of the transport robot.



The mass standard magazine offers up to 100 magazine positions, this number is conditioned by a comparator model. The device enables comparison of weights of all shapes compliant with OIML recommendations, using just one universal insert.

0.00000000

Not logged in

CAMERA 8.0 Max

10
ABBA

Comparator

Reference weight
Select reference weight

Test weight

Automatic Nano-Mass Comparator

Start control

Cycles quantity

Method

Test weight

Reference weight

Mass difference



NANO.AK-4/500

Automatic Nano-Mass Comparator

The NANO.AK-4/500 Automatic Nano-Mass Comparator enables determining mass deviations of weights with the minimum possible operator participation. The comparator allows to compare weights of mass ranging between 0.05 mg to 500 mg.

NANO.AK-4/500 Automatic Nano-Mass Comparator, due to the elimination of the human factor, temperature changes and air drafts, guarantees excellent measurement repeatability when compared to manual mass comparator.

An element that controls mass comparator operation is a digital management module, which is placed inside comparator's chamber along with an automatic mass standard feeder. Mass comparator is operated by means of indicator connected to the comparator controller. Control elements are not mechanically integrated with the construction thanks to what the influence of ambient conditions on mass comparator chamber is significantly reduced.




No other mass comparator in the world calibrates mass standards starting from 50 µg with the readability of up to 10 ng. In addition to the highest resolution and the possibility of calibration of micro-standards with the lowest measurement uncertainty, it ensures the best repeatability and the lowest sd value.



Compact device dimensions facilitate its use on a standard measurement workstation.



User-friendly and functional software guides you through preparation process of complete calibration plan within just a few minutes.



Comparison can be carried out for weights of all shapes with use of just one universal weighing pan.

UMA

Automatic Mass Comparators



Mass comparators of UMA series stand for the highest standard of professional automatic mass comparators. They provide comparison of 1 mg – 1000 g weights of E1 and lower classes.

The device is equipped with 18 or 36 magazine positions allowing to deposit up to 36 weights. This solution allows to perform either comparison for complete set of weights carried out within one process or comparison for just a few weights of the same mass.

Owing to elimination of human factor and with temperature changes and air drafts reduced to zero, UMA automatic mass comparators provide the highest possible measurement repeatability.


The UMA series, thanks to a vibration sensor inside the electronics, analyses and recognises vibrations origin. The sensor allows to determine whether the vibrations come from ground or other sources affecting the measurement result.



The weighing pan has been designed to enable measurement of very small samples with very high precision. This also secures a weight against wedging.



User-friendly and functional software guides you through preparation process of complete calibration plan within just a few minutes.



Comparison can be carried out for weights of all shapes with use of just one universal weighing pan.



Compact size guarantees operation of the device at any laboratory workstation. Possibility of comparison of many weights at a time adds to comparator's versatility.

AK-4

Automatic Mass Comparators

Mass comparators of AK-4 series stand for the highest standard of professional automatic mass comparators. They provide comparison of 10 g – 10 kg weights of E1 and lower classes. the comparators are offered in two versions:

- 4-positional weight alternator: for 1 reference mass standard and 3 tested weights
- 2-positional weight alternator: for reference weight being a combination of mass value of 3 separate weights.

Owing to elimination of human error and with temperature change and air drafts reduced to zero, AK-4 automatic mass comparators provide the highest possible measurement repeatability, incomparable to repeatability offered by manual comparators.

A supplementary external anti-draft chamber comes standard with each AK-4 comparator.



Weight positioning of sliding nature prevents errors of eccentricity.



RADWAG solutions intended for automatic comparators, i.e. positioning mechanism, guarantee extremely precise setting of weight on a weighing pan, performed each time the turntable has been rotated.



Extraordinary design of the weighing pan enables both, comparison of mass being combination of 3 weights, and standard comparison of 1 weight.



Weighing range switch allows you to select different load ranges for weights comparison. Regardless of selected option, constant comparator resolution is maintained.



Automatic Mass Comparators


AKM-2

Automatic Mass Comparators

Mass comparators of AKM-2 series stand for the highest standard of professional automatic mass comparators. They provide comparison of 500 g – 50 kg weights of E1 and lower classes. the comparator is offered in a form of 2-positional weight alternator: for 1 reference mass standard and 1 tested weight.

For maximum comfort of operation, the AKM-2 has been equipped with automatic sliding feeding mechanism allowing easy placement of heavy weights.

Owing to elimination of human error and with temperature change and air drafts reduced to zero, AKM-2 automatic mass comparators provide the highest possible measurement repeatability, incomparable to repeatability offered by manual comparators.



Weight positioning of sliding nature prevents errors of eccentricity.



Dedicated weighing pan design facilitates extremely precise weights comparison, no matter how light the weights are.



Weighing range switch allows you to select different load ranges for weights comparison. Regardless of selected option, constant comparator resolution is maintained.



Sturdy design of the table, featuring heavy granite stone and robust rubber shock absorbers, reduces effect of vibrations to the absolute minimum.



Manual Mass Comparators

UYA 5Y.KO

Manual Mass Comparators

Mass comparators of UYA 5Y.KO series stand for high standard of professional manual mass comparators. They provide comparison of 1 mg – 5 g weights of E1 and lower classes.

The UYA 5Y.KO series is characteristic for 0.1 µg readability. Significant feature of UYA 5Y.KO comparator is the automatically opened transparent weighing chamber providing maximum resistance to air drafts.

A supplementary external anti-draft chamber comes standard with each UYA 5Y.KO comparator.



Automatically opened transparent weighing chamber of UYA 5Y.KO mass comparator provides utmost visibility of the weight subjected to comparison.



Complex databases offer unlimited access to information on mass standards, customers and tasks along with preview of reports on carried out comparisons.

APP 5Y.KO

Manual Mass Comparators

Mass comparators of APP 5Y.KO series stand for high standard of professional manual mass comparators. They provide comparison of 100 g – 50 kg weights of E1 and lower classes.

APP 5Y.KO mass comparators feature model-related weighing pan type, it is either self-centering pan or weighing pan with mechanical centering aid, the former one allowing for dissemination of weights.

A supplementary external anti-draft chamber comes standard with each APP 5Y.KO comparator.



Weighing pan with mechanical centering system facilitates precise placing of mass standards, plus it reduces effect of eccentricity to zero.



Optional “floating” self-centering pan offers reduction of eccentricity effect, plus it supports dissemination of reference mass to more than one weight.

XA 5Y.KO

Manual Mass Comparators



Mass comparators of XA 5Y.A.KO series are standard manual mass comparators. They provide comparison of 1 mg – 200 g weights of E1 and lower classes.

XA 5Y.A.KO mass comparators have been equipped with transparent weighing chamber featuring automatically opened door.

XA 5Y.A.KO mass comparators serve not only comparison purposes, they can be used for weighing processes and other related operations that are typical for standard analytical balances of XA 5Y.A series.



Spacious and airtight weighing chamber of XA 5Y.A.KO mass comparator features automatically opened door.



Openwork weighing pan significantly reduces ambient conditions influence on the measurement.



Transparent weighing chamber of PS 5Y.KB mass comparator, protecting the weighing pan, provides utmost visibility of the tested weight.



Semi-automatic levelling system is a standard feature of each 5Y series mass comparator.

WAY 5Y.KO

Manual Mass Comparators



Mass comparators of WAY 5Y.KO series stand for high standard of professional manual mass comparators. They provide comparison of 1 mg – 5 kg weights of E1 and lower classes.

WAY 5Y.KO mass comparators feature transparent weighing chamber and ring-shaped draft shield encircling the weighing pan. Models characterized with the highest accuracy additionally comprise an internal box-shaped draft shield made of glass.

A supplementary external anti-draft chamber comes standard with each WAY 5Y.KO comparator*.


* Not applicable to WAY 1200.5Y.KO comparator.




Ring-shaped draft shield encircling the weighing pan, apart from protecting the pan against air drafts, prevents potential shocks that could be applied accidentally to the weighing pan while loading the weight.



Weighing pan, made of the best quality non-magnetic stainless steel, features centrally positioned markings allowing easy and precise weights placement.



Glass draft shield minimizes influence of air drafts on comparison process. the glass with special conductive coating supports discharge of static electricity.



Selected WAY 5Y.KO models allow use of supplementary external loads, with this it is possible to carry out comparison of non-standard weights.

PM 5Y.KB

Manual Mass Comparators

Mass comparators of PM 5Y.KB series are standard manual mass comparators. They provide comparison of 1 kg – 50 kg weights of F2 and lower classes.

PM 5Y.KB mass comparators have been equipped with an open-work weighing pan featuring centering holders that facilitate precise weights placement.

PM 5Y.KB mass comparators serve not only comparison purposes, they can be used for weighing processes and other related operations that are typical for standard precision balances of PM 5Y series.



Centering holders of the openwork weighing pan allow precise placement of the weights, it is especially helpful when working with heavy and large mass standards.



Dedicated box for PM 5Y.KB mass comparator is a warranty for safe transport. With in-built interfaces you have a green light for immediate operation right after opening the box.

HRP 5Y.KB

Manual Mass Comparators

Mass comparators of HRP 5Y.KB series stand for high standard of professional manual mass comparators. They provide comparison of 200 kg – 1000 kg weights of M1 and lower classes.

HRP 5Y.KB mass comparators have been equipped with large weighing platform featuring markings allowing you to place the weights centrally and precisely.

HRP 5Y.KB mass comparators serve not only comparison purposes, they can be used for weighing processes and other related operations.



Precisely marked weighing platform of HRP 5Y.KB comparator is of great help when trying to place the weight accurately in the center.



Colour 5.7" touchscreen comes standard with all RADWAG manufactured comparators.

HRP 5Y.KO

Manual Mass Comparators



Mass comparators of HRP 5Y.KO series stand for high standard of professional manual mass comparators. They provide comparison of 10 kg – 2000 kg weights of F2 and lower classes.

HRP 5Y.KO mass comparators have been equipped with large weighing platform featuring markings allowing you to place the weights centrically and precisely.

HRP 5Y.KO mass comparators serve not only comparison purposes, they can be used for weighing processes and other related operations.




Precisely marked weighing platform of HRP 5Y.KO comparator is of great help when trying to place the weight accurately in the center.




Colour 5.7" touchscreen comes standard with all RADWAG manufactured comparators.



HRP mass comparators have been equipped with special self-centering weighing pan to provide both greater comfort of operation and reduced off-center load error.



The self-centering weighing pan has been designed in order to enable stabilising and levelling of weights that are put off the center, plus to allow comparison of weights of atypical shape.



Susceptometer
Magnetization

SM-UYA, SM-MYA

Susceptometer

RADWAG-designed SM susceptometer enables determination of magnetic characteristics of mass standards of the following classes: E1, E2, F1 and F2. The device features 3 different heights, from the mass standard base to the centre of the magnet. The recommended distance between the mass standard and the magnet depends on the mass standard's class. The measurement result is magnetic susceptibility and polarisation, i.e. residual magnetism.

Modular design, upon disassembling respective module and depending on the model, enables using the susceptometer as a mass comparator or a balance.

Innovative design of the susceptometer enables verification of magnetic characteristics of 2g-50kg mass standards.

With use of modern indicator with very efficient processor, the susceptometer does not require additional external devices supporting calculations. Indicator software calculates magnetic susceptibility and polarisation, which facilitates and accelerates mass standards testing. The software automatically verifies measurements compliance with OIML R111. Mass standard status can be read on the test report.



A top-class magnet guarantees repeatability.



Positioners on the susceptometer weighing pan facilitate centring of the mass standard.



The modular design enables to use the susceptometer as a microbalance or a mass comparator.



Specially designed susceptometer weighing pan does not require any additional elements to change the measuring range of the device.

RMCS

PC Software

Radwag Multiple Comparator Software, RMCS, has been designed to enable management of laboratory-performed calibration procedures, starting from the moment of accepting an order, through its progress, until issuing a calibration certificate.

The calibration process supported by means of RMCS provides improved efficiency, reliable measurement results and complete documentation on calibration process, together with lower labour costs.


RMCS PC Software is intended for cooperation with RADWAG manufactured mass comparators. With the software you can carry out calibration processes using ABBA and ABA methods.



Radwag Multiple Comparator Software – operation scheme

RMCS PC software makes it possible to initiate the calibration procedure by means of task sent to a particular mass comparator. Additionally it features option for autonomous performance of calibration process, triggered by the mass comparator itself.

In both cases, data is transferred to the software for the purpose of registering, controlling and finally issuing a calibration certificate.



RMCS System functions

- Complete management of a calibration laboratory calibrating mass standards and weights
- Complex management of RADWAG comparators
- Calibration using ABBA and ABA methods
- Cooperation with monitoring system for ambient conditions
- Databases support: comparators, mass standards, users and calibration orders
- Bilateral data synchronization with RADWAG mass comparators
- Archiving orders, calibration certificates and ambient conditions records
- Record of events and calibration process reporting
- Export of report results and calibration certificates

Mass comparators linked in the RMCS system autonomously cooperate with THB ambient conditions modules recording ambient conditions state (temperature, humidity and atmospheric pressure) throughout the whole control process.

Measurement results are displayed and sent, in real time, to RMCS software for the purpose of process control and data archiving.

THB

Ambient Conditions Monitoring

Maintaining optimal ambient conditions at a workplace is a warranty of precise results for comparison processes.

THB monitoring system has been designed to offer option of constant ambient conditions supervision provided at the place of mass comparator operation or in any laboratory room. the system performs real-time measurement of air temperature, relative humidity and atmospheric pressure. the measured values are then used for calculation of air density and dew point temperature.


The measurements carried out for a particular workstation are performed by means of its local sensors – THB Ambient Conditions Modules. Current state of given measurements is displayed on the comparators terminal along with messages informing on critical values, all this thanks to connection established between the THB module and the comparator.



Ambient Conditions Monitoring performed for separate laboratory rooms - operation scheme

Measurements results of particular THB modules are transferred in real time to THB-R recorder. the recorder supports up to 16 modular sensors, thus allowing monitoring of ambient conditions in multiple points in the proximity of up to 1200 m.

THB-Multi software enables displaying the measurements results on the computer screen. Additionally it offers data analysis, reports and graphs preparation and measurements record in database.



Basic parameters for THB Ambient Conditions Modules

Measured temperature range	+5 °C – +45 °C
Temperature measurement accuracy	d = 0.01 °C / error ± 0.1 °C
Measured pressure range	850 – 1050 hPa
Pressure measurement accuracy	d = 0.1 hPa / error ± 2 hPa
Measured humidity range	0 – 100 %
Humidity measurement accuracy	d = 0.1 % / error ± 2 % (from 0 % to 10 % and from 90 % to 100 % the accuracy is 5 %)

According to OIML and ASTM

Errors for weights

According to OIML and ASTM guidelines mass standards and weights, used for mass measurement purposes, are divided into accuracy classes: E1, E2, F1, F2, M1, M2 and M3 (OIML classification) or 1 – 7 (ASTM classification).

In the course of calibration of mass standards and weights the measurement uncertainty for coverage factor $k = 2$ (with confidence of about 95%) shall not be greater than 1/3 of maximum error value specified for a particular mass standard or weight of a given class or nominal value.

Maximum permissible errors according to OIML R 111-1

±δm in mg


Nominal value	Class E1	Class E2	Class F1	Class F2	Class M1	Class M1-2	Class M2	Class M2-3	Class M3
1 mg	0.003	0.006	0.02	0.06	0.2				
2 mg	0.003	0.006	0.02	0.06	0.2				
5 mg	0.003	0.006	0.02	0.06	0.2				
10 mg	0.003	0.008	0.025	0.08	0.25				
20 mg	0.003	0.01	0.03	0.1	0.3				
50 mg	0.004	0.012	0.04	0.12	0.4				
100 mg	0.005	0.016	0.05	0.16	0.5		1.6		
200 mg	0.006	0.02	0.06	0.2	0.6		2		
500 mg	0.008	0.025	0.08	0.25	0.8		2.5		
1 g	0.01	0.03	0.1	0.3	1		3		10
2 g	0.012	0.04	0.12	0.4	1.2		4		12
5 g	0.016	0.05	0.16	0.5	1.6		5		16
10 g	0.02	0.06	0.2	0.6	2		6		20
20 g	0.025	0.08	0.25	0.8	2.5		8		25
50 g	0.03	0.1	0.3	1	3		10		30
100 g	0.05	0.16	0.5	1.6	5		16		50
200 g	0.1	0.3	1	3	10		30		100
500 g	0.25	0.8	2.5	8	25		80		250
1 kg	0.5	1.6	5	16	50		160		500
2 kg	1	3	10	30	100		300		1 000
5 kg	2.5	8	25	80	250		800		2 500
10 kg	5	16	50	160	500		1 600		5 000
20 kg	10	30	100	300	1 000		3 000		10 000
50 kg	25	80	250	800	2 500	5 000	8 000	16 000	25 000
100 kg		160	500	1 600	5 000	10 000	16 000	30 000	50 000
200 kg		300	1 000	3 000	10 000	20 000	30 000	60 000	100 000
500 kg		800	2 500	8 000	25 000	50 000	80 000	160 000	250 000
1 000 kg		1 600	5 000	16 000	50 000	100 000	160 000	300 000	500 000
2 000 kg			10 000	30 000	100 000	200 000	300 000	600 000	1 000 000
5 000 kg			25 000	80 000	250 000	500 000	800 000	1 600 000	2 500 000

Maximum permissible errors according to ASTM E617 – 13


±δm in mg

Nominal value	Class 000	Class 00	Class 0	Class 1	Class 2	Class 3	Class 4	Class 5	Class 6	Class 7
0.05 mg	0.002	0.003	0.005							
0.1 mg	0.002	0.003	0.005	0.01						
0.2 mg	0.002	0.003	0.005	0.01	0.014					
0.3 mg	0.002	0.003	0.005	0.01	0.014	0.025				
0.5 mg	0.002	0.003	0.005	0.01	0.014	0.025	0.05	0.05	0.1	
1 mg	0.002	0.003	0.005	0.01	0.014	0.025	0.05	0.05	0.1	
2 mg	0.002	0.003	0.005	0.01	0.014	0.025	0.05	0.06	0.2	
3 mg	0.002	0.003	0.005	0.01	0.014	0.026	0.052	0.07	0.2	
5 mg	0.002	0.003	0.005	0.01	0.014	0.028	0.055	0.08	0.2	
10 mg	0.002	0.003	0.005	0.01	0.014	0.03	0.06	0.1	0.5	0.4
20 mg	0.002	0.003	0.005	0.01	0.014	0.035	0.07	0.12	0.5	0.56
30 mg	0.002	0.003	0.005	0.01	0.014	0.038	0.075	0.14	0.5	0.68
50 mg	0.002	0.003	0.005	0.01	0.014	0.042	0.085	0.16	0.5	0.88
100 mg	0.002	0.003	0.005	0.01	0.025	0.05	0.1	0.2	1	1.2
200 mg	0.002	0.003	0.005	0.01	0.025	0.06	0.12	0.26	1	1.8
300 mg	0.002	0.003	0.005	0.01	0.025	0.07	0.14	0.3	1	2.2
500 mg	0.002	0.003	0.005	0.01	0.025	0.08	0.16	0.38	1	3
1 g	0.005	0.01	0.017	0.034	0.054	0.1	0.2	0.5	2	4.5
2 g	0.005	0.01	0.017	0.034	0.054	0.13	0.26	0.75	2	7
3 g	0.005	0.01	0.017	0.034	0.054	0.15	0.3	0.95	2	9.4
5 g	0.005	0.01	0.017	0.034	0.054	0.18	0.36	1.3	2	13
10 g	0.01	0.02	0.025	0.050	0.074	0.25	0.5	2	2	21
20 g	0.013	0.025	0.037	0.074	0.1	0.35	0.7	3	3	33
30 g	0.014	0.026	0.037	0.074	0.15	0.45	0.9	4	5	44
50 g	0.015	0.03	0.06	0.12	0.25	0.6	1.2	5.6	7	62
100 g	0.025	0.05	0.13	0.25	0.5	1	2	9	10	100
200 g	0.05	0.1	0.25	0.50	1	2	4	15	20	160
300 g	0.075	0.15	0.38	0.75	1.5	3	6	20	30	210
500 g	0.13	0.25	0.6	1.2	2.5	5	10	30	50	300
1 kg	0.25	0.50	1.3	2.5	5	10	20	50	100	470
2 kg	0.5	1	2.5	5	10	20	40	100	200	750
3 kg	0.75	1.5	3.8	7.5	15	30	60	150	300	1 000
5 kg	1.3	2.5	6	12	25	50	100	250	500	1 400
10 kg	2.5	5	13	25	50	100	200	500	1 000	2 200
20 kg	5	10	25	50	100	200	400	1 000	2 000	3 800
25 kg	6.25	12.5	31	62	125	250	500	1 200	2 500	4 500
30 kg	7.5	15	38	75	150	300	600	1 500	3 000	4 500
50 kg	13	25	63	125	250	500	1 000	2 500	5 000	7 500
100 kg					500	1 000	2 000	5 000	10 000	15 000
200 kg					1000	2 000	4 000	10 000	20 000	30 000
300 kg					1500	3 000	6 000	15 000	30 000	45 000
500 kg					2 500	5 000	10 000	25 000	50 000	75 000
1 000 kg					5 000	10 000	20 000	50 000	100 000	150 000
2 000 kg					10 000	20 000	40 000	100 000	200 000	300 000
3 000 kg					15 000	30 000	60 000	150 000	300 000	450 000
5 000 kg					25 000	50 000	100 000	250 000	500 000	750 000


Calibration range for weights according to OIML R111




Calibration range for weights according to OIML R111



Calibration range for weights according to ASTM E617



Calibration range for weights according to ASTM E617



Technical Specification

Automatic and Robotic Mass Comparators

Automatic Vacuum Mass Comparators



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-417-0003	AVK 1000.5Y	1002 g	0.1 µg	0.4 µg	ø100 mm

Density Measurement



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-418-0004	AGV-8 1000.5Y	1110 g	0.01 mg	0.04 mg	ø60 mm
WL-418-0005	AGV-2 20.5Y	26.1 kg	1 mg	2 mg	ø220 mm self centering

Robotic Mass Comparators



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-419-0011	RMCM 5.5Y	6.1 g	0.1 µg	0.25 µg	24x50 mm
WL-419-0009	RMCM 10	10.3 g	0.1 µg	0.15 µg	50x40 mm
WL-419-0012	RMCM 100.5Y	110 g	1 µg	1.5 µg	24x63 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-419-0013	RMC 100.1.5Y	106 g	0.1 µg	0.5 µg	24x63 mm
WL-419-0014	RMC 1000.1.5Y	1060 g	1 µg	1.2 µg	50x125 mm

Automatic Nano-Mass Comparators



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-413-0023	NANO.AK-4.500.5Y	510 mg	10	0.04 µg	ø20 mm

Automatic Mass Comparator UMA



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-415-0004	UMA 5.5Y	6.1 g	0.0001 mg	0.2 µg	ø20 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-415-0005	UMA 100.5Y	110 g	0.001 mg	1.5 µg	ø21 mm
WL-415-0006	UMA 1000.5Y	1060 g	0.005 mg	8 µg	ø48 mm

Automatic Mass Comparator AK-4



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-413-0014	AK-4.100.5Y	110 g	0.001 mg	1.5 µg	ø24 mm
WL-413-0010	AK-4.100.1.5Y	110 g	0.1 µg	0.8 µg	ø24 mm
WL-413-0016	AK-4.1000.5Y	1.02 kg	0.005 mg	8 µg	ø50 mm
WL-413-0017	AK-4.1001.5Y	1.02 kg	0.001 mg	1.7 µg	ø50 mm
WL-413-0005	AK-4.2000.5Y	2.05 kg	0.01 mg	12 µg	ø75 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-413-0018	AK-4.5000.5Y	5.05 kg	0.01 mg	15 µg	ø75 mm
WL-413-0019	AK-4.5000.1.5Y	5.05 kg	0.1 mg	0.08 mg	ø75 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-413-0021	AK-4.10000.5Y	10.05 kg	0.01 mg	15 µg	ø100 mm

Automatic Mass Comparator AKM-2



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-411-0012	AKM-2.10.5Y	10.2 kg	0.1 mg	0.15 mg	ø90 mm
WL-411-0013	AKM-2.20.5Y	20.5 kg	0.1 mg	0.3 mg	ø90 mm
WL-411-0014	AKM-2.50.5Y	51 kg	1 mg	2.5 mg	ø100 mm

Technical Specification

Manual Mass Comparators

Manual Mass Comparators UYA 5Y.KO



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-408-0007	UYA 6.5Y.KO	6.1 g	0.1 µg	0.2 µg	ø16 mm

Manual Mass Comparators XA 5Y.KO



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-405-0020	XA 6.5Y.KO	6 g	0.001 mg	1.2 µg	ø16 mm
WL-405-0021	XA 21.5Y.KO	21 g	0.001 mg	1.2 µg	ø24 mm
WL-405-0022	XA 52.5Y.KO	52 g	0.005 mg	2.5 µg	ø24 mm
WL-405-0023	XA 200.5Y.KO	210 g	0.01 mg	0.005 mg	ø90 mm

Manual Mass Comparators WAY 5Y.KO



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-406-0039	WAY 100.5Y.KO	110 g	0.001 mg	2.5 µg	ø30 mm
WL-406-0040	WAY 200.5Y.KO	210 g	0.001 mg	3 µg	ø40 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-406-0041	WAY 500.5Y.KO	520 g	0.01 mg	0.012 mg	ø50 mm
WL-406-0038	WAY 1.5Y.KO	1.02 kg	0.01 mg	0.25 mg	ø60 mm
WL-406-0042	WAY 1200.5Y.KO	1200 g	0.1 mg	0.08 mg	ø80 mm
WL-406-0043	WAY 2.5Y.KO	2.3 kg	0.1 mg	0.08 mg	ø70 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-406-0044	WAY 5.5Y.KO	5.05 kg	0.1 mg	0.15 mg	ø90 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-406-0045	WAY 5100.5Y.KO	5100 g	1 mg	0.8 mg	ø100 mm

Manual Mass Comparators APP



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-407-0036	APP 10.5Y.KO	10.2 kg	0.1 mg	0.35 mg	ø190 (ø300) mm
WL-407-0037	APP 30.5Y.KO	30.5 kg	1 mg	3 mg	ø220 (ø300) mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-407-0038	APP 64.5Y.KO	64 kg	10 mg	13 mg	ø300 (ø400) mm

Manual Mass Comparators PM 5Y.KB



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-416-0004	PM 25.5Y.KB	25.5 kg	10 mg	4 mg	302x252 mm
WL-416-0005	PM 50.5Y.KB	51 kg	100 mg	70 mg	302x252 mm

Mass Comparators HRP 5Y.KO



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-414-0023	HRP 150.1.5Y.KO	151 kg	0.05 g	0.1 g	800x600 mm
WL-414-0026	HRP 500.1.5Y.KO	510 kg	0.1 g	0.2 g	1000x800 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-414-0024	HRP 200.5Y.KO	210 kg	0.2 g	0.4 g	800x600 mm
WL-414-0025	HRP 500.5Y.KO	510 kg	0.5 g	0.6 g	800x600 mm
WL-414-0027	HRP 1000.5Y.KO	1050 kg	1 g	1.5 g	1000x800 mm



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-414-0028	HRP 2000.5Y.KO	2100 kg	2 g	2.5 g	1250x1000 mm
WL-414-0029	HRP 2000.1.5Y.KO	2100 kg	5 g	5 g	1250x1000 mm

Mass Comparators HRP 5Y.KB



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-414-0030	HRP 1000.5Y.KB	1050 kg	10 g	6 g	1000x800 mm

Technical Specification

Susceptometer



Product Code	Model	Max. capacity	Readability	Repeatability	Weighing pan dimensions
WL-101-1083	SM-UYA 3.5Y	50 kg	0.1 µg	ø300 mm	2000, 800, 200 A/m
WL-408-0008	SM-UYA 6.5Y.KO	50 kg	0.1 µg	ø300 mm	2700, 2000, 800, 380, 200 A/m
WL-101-1084	SM-MYA 5.5Y	50 kg	1 µg	ø300 mm	2000, 800, 200 A/m
WL-101-1085	SM-MYA 11.5Y	50 kg	1 µg	ø300 mm	2000, 800, 200 A/m



PRODUCT CATALOGUE

ADVANCED WEIGHING TECHNOLOGIES





Environmental Protection

In ambient air quality and particulate matter emission testing.

Air quality test at the workstation.

MEASUREMENT



robotic



automatic



manual

MEASUREMENT RESOLUTION




10 µg



1 µg



0.1 µg



www.radwag.com